



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® FAST 'N FINAL® Lightweight Spackling

PRODUCT DESCRIPTION

DAP® FAST 'N FINAL® Lightweight Spackling lets you patch and prime in one easy step, saving time and money. Dries fast with no need to sand or prime, letting you paint in minutes. It is easy to apply with one strike of the putty knife. Won't shrink or crack. Ideal for repairing holes, cracks and dents in drywall, plaster, wood and stucco. DAP FAST 'N FINAL Lightweight Spackling is low in odor and for interior or exterior use.



PACKAGING	COLOR	UPC
88.7 mL Knife Cap Tube	White	7079874877
237 mL Tub	White	7079823030
473 mL Tub	White	7079823050
946 mL Tub	White	7079871354

KEY FEATURES

- **Patch & Prime in One Step**
- **Fast Drying – 30-minute Paint Ready**
- **No Sanding**
- **Won't Sink or Shrink**
- **Interior/Exterior use**

SUGGESTED USES

Ideal for filling holes, cracks, dents and defects on:

- Drywall
- Plaster
- Wood
- Stucco
- Brick



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

FOR BEST RESULTS

- Do not apply when temperatures are below 4°C.
- Do not apply outside if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior applications, first apply exterior-grade primer, then apply spackling and finish with coating of quality exterior-grade paint.
- Do not use for tuck pointing applications on brick.

APPLICATION

1. Surface must be clean, dry and free of all foreign material. For tubs, stir thoroughly before use. When using a squeeze tube, twist/unscrew the putty knife from the squeeze tube and remove the foil seal. Twist/screw the putty knife back onto the squeeze tube. Remove the cap from the tip and apply spackling, holding the flat edge against the wall, and squeeze spackling directly through the nozzle of the putty knife onto the surface your repairing.
2. Using the built-in putty knife, press spackling into hole or crack.
3. Draw putty knife firmly across the surface to remove excess material in one strike.
4. For a smoother finish, dip putty knife into water and lightly smooth spackling.
5. One application is usually sufficient for small repairs.
For repairs deeper than 1/8", apply two or more layers allowing spackling to dry between applications.
6. May be painted within minutes with a latex paint. Please follow paint manufacturer's instructions for application.
7. If sanding is desired, or if an oil-based paint is to be used, allow to dry thoroughly (approximately 24 hours).

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Thick Paste
Vehicle	Latex Polymer
Volatile	Water
Filler	Inert Filler
Odor	Mild
Paint	Takes either oil or latex-based paint



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Solids	75%
Application Temperature	4°C or higher
Service Temperature	-28°C to 65°C
Shelf Life	12 months
Freezing	Freeze/thaw stable 5 cycles at -17°C
Dry Time	30 minutes depending on temperature, humidity, and depth of fill

CLEAN UP & STORAGE

Wash tools immediately after use with soap and water. Dried material must be removed by scraping or sanding. Be sure container lid/cap is closed and tightly sealed and store in a cool, dry place away from extreme heat or cold.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.ca or by calling **888-DAP-TIPS**.

WARRANTY

DAP Canada, DAP Products Inc. and their respective affiliates will not accept liability for more than replacement product or sales price refund under any circumstances.

COMPANY IDENTIFICATION

Manufactured for: DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON, M1X 1B7

Usage Information: Call 888-DAP-TIPS or visit dap.ca & click on "Ask the Expert"

Order Information: 800-668-9397 or 416-321-1522

Fax Number: 416-321-3325

Also visit the DAP website at dap.ca