



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® MOUSE SHIELD™ SEALANT– Cream

PRODUCT DESCRIPTION

DAP® Mouse Shield™ is specifically treated to block mice, birds, bats, tree squirrels and other pests such as ants, roaches, and spiders. Use Mouse Shield to fill gaps and cracks inside your garage, attic, crawl space, basement, under sinks, around pipe / electrical penetrations or any areas where pests, insects, or drafts can enter your home and living spaces.



PACKAGING	Case	COLOUR	SKU	UPC
340g (12 oz) Can	12	Cream	7565012507	0 7565041612 9
454g (16 oz) Can	12	Cream	7565041612	0 7565012507 6

Meets ASTM E84/UL 723, Class A Fire Rated Classified



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

KEY FEATURES & BENEFITS

- Specially treated to block mice, birds, bats, tree squirrels & other pests
- Safe to use and contains no lingering odor
- Air seals and insulates to save on energy costs
- Tack-free in 15 minutes and dries in 4 hours
- Paintable / Sandable
- For internal use only

SUGGESTED USES

USE TO FILL AND SEAL:

- Gaps and voids in foundations, attics, crawlspaces
- Pipe and electrical through penetrations in cabinetry and through flooring
- Garages and outdoor sheds

FOR BEST RESULTS

- Apply in temperatures between 16°C - 38°C (60°F to 100°F)
- Surface must be free of oil and dirt for adhesion
- Dispense in the UPSIDE-DOWN position
- Apply in spaces with 40% relative humidity or greater
- Use around, not inside, junction boxes

APPLICATION

DIRECTIONS: Important – read all directions and cautions before use. Always wear gloves, eye protection and work clothes. Use drop cloths. Product is flammable during dispensing – turn off sources of ignition prior to use.

Preparation: To promote adhesion surface must be free of oil and dirt. Assemble straw and adapter, then carefully screw the trigger assembly onto valve. With trigger assembly attached, shake well for 30 seconds. Holding the can upside-down, slowly activate trigger until foam begins to dispense. Important: Before starting the job, first practice dispensing onto scrap materials.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Application: For best results this product should only be dispensed in the UPSIDE_DOWN position and apply in spaces with 40% greater relative humidity. Fill gap no more than 1/3 full, allowing room for expansion. Do not overfill. Important: Foam will continue to dispense for a few seconds after releasing the trigger – keep the straw tip moving to reduce the possibility of overfilling. Foam is tack-free in 30 minutes and dries in 4 hours. Excess foam can be trimmed, sanded, caulked or plastered as necessary. Direct sunlight discolors foam if not painted or covered.

Clean-up: If wet foam contacts skin, clean immediately with a dry rag – do not use water – water accelerates curing. Cured foam must be removed mechanically from surfaces. Uncured foam can be cleaned from most surfaces with Foam Cleaner or acetone. Do not attempt to remove cured solvents. If foam dries on skin, apply generous amounts of petroleum jelly, put on plastic gloves and wait 1 hour. With a clean cloth, firmly wipe off residue and repeat process if necessary. DO NOT use acetone or other solvents to remove product from skin.

Storage/Re-Use: Stop & restart up to 3 weeks later. To store unused portion, bend straw back onto the knob atop the dispensing trigger. Store can upright below 90° F (33°C). Product can be reused within three weeks if stored properly. To re-use, cut the end of the straw (removing any cured foam), shake well and apply as directed.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Yield per can (3/8" bead) ASTM C1536	340 g (12 oz) 454 g (16 oz)	125 meters (410 linear feet) 156 meters (512 linear feet)
Dry Time/ tack free		< 30 minutes
Cure Time		4 hours
Shelf Life		18 months (unopened)
Application Temperature Range		16°C to 38°C (60°F to 100°F)
Cutable		< 2 hours
International Building Code		compliant
International Residential Code		compliant
UL Classified Caulking & Sealants		Listed
UL 723 Surface Burning Characteristics Fire Test (Flame/Smoke)		10/15

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or calling 888-DAP-TIPS.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

WARRANTY

DAP Canada will not accept liability for more than replacement product or sales price refund under any circumstances.

COMPANY IDENTIFICATION

Manufactured for: DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON, M1X 1B7

Usage Information: Call 888-DAP-TIPS or visit dap.ca & click on "Ask the Expert"

Order Information: 800-668-9397 or 416-321-1522

Fax Number: 416-321-3325

Also visit the DAP website at dap.ca

R14175
1L15



UNDERWRITERS LABORATORIES INC.
CLASSIFIED CAULKING AND SEALANT
Surface Burning Characteristics
Applied To Inorganic Reinforced
Cement Board*
Flame Spread 10 Smoke
Developed 15

*TESTED AS APPLIED IN TWO 3/4" DIAMETER
BEADS 8" ON CENTER COVERING 8.3% OF THE
EXPOSED TEST SAMPLE AREA.