SDS Number: 1042765 Revision Date: 4/11/2022 SAP Number:



# Safety Data Sheet

24 Hour Emergency Phone Numbers Medical/Poison Control:

In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison control center

Transportation/National Response Center:

> 1-800-535-5053 1-352-323-3500

NOTE: The National ResponseCenter emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

### 1. Identification

**Product UPC Number:** 

This Safety Data Sheet is available in American Spanish upon request. Los Datos de Serguridad pueden obtenerse en Espanol si lo riquiere.

4/11/2022 Textured Concrete Latex Filler & Sealant **Revision Date: Product Name:** 

070798743328 **New SDS** 

1042765 **Product Use/Class:** Caulking Compound SDS No:

**DAP Canada** DAP Global Inc. Manufacturer: Imported by:

2400 Boston Street Suite 200 475 Finchdene Square Unit 5

Baltimore, MD 21224-4723 Scarborough, Ontario M1X 1B7 888-327-8477 (non - emergency matters) 888-327-8477 (non - emergency

Supercedes Date:

matters) SDS Coordinator: MSDS@dap.com

SDS Coordinator:

MSDS@dap.com Emergency Telephone: 1-800-535-5053, 1-352-323-3500, 1-800-222-1222

**Emergency Telephone:** 1-800-535-5053. 1-352-323-3500

Regulatory and Environmental Affairs Preparer:

### 2. Hazards Identification

#### **GHS Classification**

Not a hazardous substance or mixture.

#### Symbol(s) of Product

None

#### Signal Word

Not a hazardous substance or mixture.

#### Possible Hazards

39% of the mixture consists of ingredients of unknown acute toxicity

# 3. Composition/Information on Ingredients

<u>Chemical Name</u>	CAS-No.	Wt. %	GHS Symbols	<b>GHS Statements</b>
Limestone	1317-65-3	15-40	No Information	No Information
Dipropylene glycol dibenzoate	27138-31-4	5-10	No Information	No Information
Magnesium-alumino-silicate	1318-00-9	1-5	No Information	No Information
Glycol ethers	Proprietary	0.1-1.0	No Information	No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

#### 4. First-aid Measures

**FIRST AID - INHALATION:** Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: In case of contact, wash skin immediately with soap and water.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

# 5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: None Known.

**SPECIAL FIREFIGHTING PROCEDURES:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Spray or Fog, Water

#### 6. Accidental Release Measures

**ENVIRONMENTAL MEASURES:** Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate. Dispose of saturated absorbent or cleaning materials appropriately. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

### 7. Handling and Storage

**HANDLING:** KEEP OUT OF REACH OF CHILDREN!DO NOT TAKE INTERNALLY. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling.

**STORAGE:** Avoid excessive heat and freezing. Do not store at temperatures above 120 °F (49 °C). Store away from caustics and oxidizers.

# 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u> <u>ACGIH TLV-TWA</u> <u>ACGIH-TLV STEL</u> <u>OSHA PEL-TWA</u> <u>OSHA PEL-CEILING</u>

Limestone N.E. N.E. 15 mg/m3 TWA N.E.

total dust, 5 mg/m3 TWA respirable

fraction

Dipropylene glycol dibenzoateN.E.N.E.N.E.N.E.N.E.Magnesium-alumino-silicateN.E.N.E.N.E.N.E.N.E.Glycol ethersN.E.N.E.N.E.N.E.N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

#### **Personal Protection**



RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.



SKIN PROTECTION: Rubber gloves.



**EYE PROTECTION:** Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



**HYGIENIC PRACTICES:** Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

# 9. Physical and Chemical Properties

Appearance:
Odor:
Slight
Density, g/cm3:
1.40 - 1.40
Freeze Point, °C:
Not Established
Not Established
Decomposition Temperature, °C:
Boiling Range, °C:
Minimum Flash Point, °C:
Gray
Slight
1.40 - 1.40
Not Established
100 - 100
100

Evaporation Rate: Slower Than n-Butyl Acetate

Vapor Density: Heavier Than Air

Combustible Dust: Does not support combustion

Physical State: Paste

Odor Threshold: Not Established Between 7.0 and 12.0 pH: Viscosity (mPa.s): Not Established Partition Coeff., n-octanol/water: Not Established **Explosive Limits, %:** N.E. - N.E. Auto-Ignition Temperature, °C Not Established Vapor Pressure, mmHg: Not Established Flash Method: Seta Closed Cup

Flammability, NFPA: Non-Flammable

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

# 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., COx, NOx.

# 11. Toxicological Information

**EFFECT OF OVEREXPOSURE - INHALATION:** Under normal use conditions, this product is not expected to cause adverse health effects. Inhalation of vapors in high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury.

**CARCINOGENICITY:** No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Repeated or prolonged exposure may cause mild irritation of eyes and skin. Constituents of this product include crystalline silica which ,if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

PRIMARY ROUTE(S) OF ENTRY: Skin Contact

#### **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u> 1317-65-3	<u>Chemical Name</u> Limestone	Oral LD50 6450 mg/kg Rat	<u>Dermal LD50</u> N.I.	Vapor LC50 N.I.
27138-31-4	Dipropylene glycol dibenzoate	5368 mg/kg Rat	>2000 mg/kg Rabbit	>200 mg/L Rat
1318-00-9	Magnesium-alumino-silicate	N.I.	N.I.	N.I.
SEQ548	Glycol ethers	N.I.	N.I.	N.I.

N.I. = No Information

# 12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

# 13. Disposal Information

**DISPOSAL INFORMATION:** This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

# 14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT UN/NA Number: N.A.

**DOT Proper Shipping Name:** Not Regulated

DOT Technical Name: N.A.

DOT Hazard Class: N.A.

Hazard SubClass: N.A.

Packing Group: N.A.

# 15. Regulatory Information

#### **SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

### 16. Other Information

Revision Date: 4/11/2022 Supersedes Date: New MSDS

Reason for revision: HazCom2012/GHS Conversion

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 

Health:Flammability:Reactivity:Personal Protection:100X

VOC Less Water Less Exempt Solvent, g/L: 35.1

VOC Material, q/L: 23

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 0.04

VOC Actual, Wt/Wt%: 1.6

#### Icons for GHS Pictograms shown in Section 3 describing each ingredient:

No GHS Pictograms exist for Section 3

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.