



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Concrete Crack Filler

PRODUCT DESCRIPTION

DAP® Concrete Crack Filler is a one-of-a-kind, water-activated dry powder that creates a seamless repair in one-pass. Ready-to-use; no shaking or mixing required. Once applied & dampened it hardens to permanently fill & repair cracks. Resists UV fading, cracking & shrinking. The low dust, easy-to-pour formula effectively fills horizontal cracks for a fast & easy repair. To use, prep surface, fill crack, level & mist. Use as is. DO NOT mix with other products. Interior/Exterior use.



PACKAGING	COLOUR	SKU	UPC
737 g bottle	Concrete	7079870500	0 7079870500 5

KEY FEATURES & BENEFITS

- Ideal for horizontal cracks in concrete, stone & other masonry
- Repairs cracks up to 12.7 mm W x 12.7mm D in a single pass.
- Light foot traffic ready in 4 hours
- Strong and durable repair
- Resistant to shrinkage, UV fading, & cracking
- Low dust, no odour
- Easy clean-up
- Interior/exterior



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

USE FOR REPAIRING CRACKS:

- Concrete sidewalks & driveways
- Patio pavers
- Landscaping stones
- Ceramic tiles
- Cement blocks or bricks

ADHERES TO:

- Brick
- Stone
- Concrete
- Mortar
- Fiber Cement

FOR BEST RESULTS

- Apply in temperatures above 1.7°C (35°F)
- Crack/joint width should not exceed 12.7mm (½ inch)
 - For cracks that exceed 12.7mm (½ inch) in depth, apply product in 12.7mm (½ inch) layers letting it fully dry in between each application.
- Do not apply when rain or freezing temperatures are forecasted within 24 hours
- To activate, use clean water from a light mist setting on a gardening hose or spray bottle
- Do not flood the repair, or allow water to pool on the surface
- Store away from moisture

APPLICATION

Product Application

1. Surface must be clean, dry, structurally sound, and free of all foreign material.
2. Remove the cap & cut spout at a 45° angle to desired size.
3. Fill void, slightly overfilling. Use as is. DO NOT mix with other products.
4. Using a brush, trowel, or gloved finger lightly level surface to a feathered edge.
5. To activate, lightly mist the area using a spray bottle or mist setting on gardening hose with clean water, being sure not to flood the area. Overwatering may cause poor performance and displace the crack filler.
6. Repaired area is ready for light traffic in 4 hours, fully dried in 24 hours.
7. Clean up excess materials with a brush. Dried material-must be scraped away.
8. Replace cap & tightly seal for storage and reuse. Store product below 26.7°C (80°F) & away from moisture.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Dry Powder
Base Polymer	Advanced acrylic polymer
Volatile	Water
Weight % Solids	100%
Density (lbs per gallon)	24.9
Odour	No odour
Clean Up	Water
Shelf Life	3 years
Coverage	Up to 10.4 meters (34 linear feet) based on 12.7mm depth x 12.7mm width (½ inch depth, ½ inch width)
Typical Application Properties	
Application Temperature Range	Above 1.7°C (35° F)
Light Traffic Ready	4 hours
Return to Service Time	A minimum of 24 hours drying time is required prior to allowing significant foot traffic and 48 hours for vehicular traffic.
Typical Cured Performance Properties	
Service Temperature Range	Above 1.7°C (35° F)
Water/Rain Ready Time	24 hours
Miscellaneous	Cured (inhibits weed growth and insects)

CLEAN UP & STORAGE

Clean dry powder by sweeping and collecting the material. Dried material must be mechanically scraped, chipped or ground away. Close container tightly and store any remaining powder in a cool, dry place.

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS sheet by visiting our website at dap.ca or by calling 888-DAP-TIPS.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

WARRANTY

If product fails to perform when used as directed, call 888-DAP-TIPS for replacement product or sales price refund. DAP Canada will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufactured for: DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON, M1X 1B7

Usage Information: Call 888-DAP-TIPS or visit dap.ca & click on "Ask the Expert"

Order Information: 800-668-9397 or 416-321-1522

Fax Number: 416-321-3325

Also visit the DAP website at dap.ca