



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® KWIK SEAL® KITCHEN & BATH ADHESIVE CAULK

### PRODUCT DESCRIPTION

DAP® KWIK SEAL® KITCHEN & BATH ADHESIVE CAULK is an easy-to-use acrylic latex that bonds like a glue and seals like a caulk. Once cured, it is mould and mildew resistant and 100% waterproof seal. It is easy to apply, paintable, low in odour and water clean-up. Interior use.



PACKAGING	COLOUR	UPC
300 mL (10.1 fl oz) Cartridge	White	7079871018
162 mL (5.5 fl oz) Tube	White	7079874853

### KEY FEATURES & BENEFITS

- Cured caulk is mould & mildew resistant
- 100% waterproof seal
- Bonds like glue, seals like a caulk
- Paintable
- Easy water clean-up & low odour
- VOC compliant
- Interior use

### SUGGESTED USES

#### USE FOR CAULKING & SEALING:

- Tubs
- Showers
- Sinks
- Backsplashes
- Vanities
- Countertops
- Fixtures
- Pipes
- Repairing loose tiles



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## ADHERES TO:

- Wood – painted & unpainted
- Ceramic
- Porcelain
- Glass
- Most metals
- Most plastics
- Drywall
- Plaster
- Brick
- Stone
- Most common building materials

## FOR BEST RESULTS

- Apply in temperatures above 4.4°C.
- Not for continuous underwater use, high temperature surfaces or surface defects.
- Joint size should not exceed 9 mm (3/8") wide x 9 mm (3/8") deep. If joint depth exceeds 9 mm (3/8"), use backer rod material.
- **Wait 36 hours before exposing to water.**
- Store caulk away from extreme heat or cold.

## APPLICATION

### Surface Preparation

Surface must be clean, dry, structurally sound and free of all old caulk, dirt and other foreign material. Rubbing alcohol (Isopropyl alcohol) is recommended for removing soap film and soil.

### Product Application

1. If using the squeeze tube, remove cap.
2. Cut nozzle at 45° angle to desired bead size.
3. If using the cartridge, load into caulk gun.
4. Fill gap or joint with caulk.
5. If necessary, tool or smooth the bead of caulk with a finishing tool before caulk skins over.
6. Clean up excess wet caulk with a damp sponge before it skins over. Excess dried caulk must be cut or scraped away. Clean hands and tools with warm water and soap.
7. Allow caulk to dry at least 2 hours (longer in cool/humid conditions) before painting with latex or oil-based paints.
8. **Wait 36 hours before exposing to water.**
9. Reseal container for storage and reuse.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

<b>Typical Uncured Physical Properties</b>	
Appearance/Consistency	Gunnable, non-sag paste
Base Polymer	Siliconized acrylic polymer
Filler	Not applicable
Volatile	Water
Weight % Solids	78%
Density (lbs per gallon)	12.6
Odour	Very mild
Clean Up	Water
Flash Point	>100°C
Freeze Thaw Stability (ASTM C1183)	Passes 5 cycles
Shelf Life	12 months
Coverage	300 ml (10.1 fl oz): 17 linear meters (55 linear feet) at a 5 mm (3/16") diameter bead 162 ml (5.5 fl oz): 9 linear meters (30 linear feet) at a 5 mm (3/16") diameter bead
<b>Typical Application Properties</b>	
Application Temperature Range	4.4°C to 37°C
Tooling Time (Working Time)	60 minutes
Tack Free Time	60 minutes
Full Dry Through	36 hours
Return to Service Time	36 hours
Vertical Sag (ASTM D2202)	1 mm (0.05")
<b>Typical Cured Performance Properties</b>	
Service Temperature Range	-29°C to 82°C
Water Ready Time	36 hours
Paint Ready Time	2 hours
Mildew Resistance	Cured caulk is mould & mildew resistant



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## CLEAN UP & STORAGE

Clean up excess wet caulk with a damp sponge before it skins over. Excess dried caulk must be cut or scraped away. Clean hands and tools with warm water and soap. Store container in a cool, dry place away from extreme heat or cold.

## SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.ca](http://dap.ca) or calling 1-888-DAP-TIPS.

## WARRANTY

DAP Canada, DAP Products Inc. and their respective affiliates will not accept liability for more than replacement product or sales price refund under any circumstances.

## COMPANY IDENTIFICATION

**Manufactured for:** DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON, M1X 1B7

**Usage Information:** Call 888-DAP-TIPS or visit [dap.ca](http://dap.ca) & click on "Ask the Expert"

**Order Information:** 800-668-9397 or 416-321-1522

**Fax Number:** 416-321-3325

**Also visit the DAP website at [dap.ca](http://dap.ca)**