



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## MONO<sup>®</sup> SILICONE MAX<sup>™</sup> Premium Kitchen, Bath & Plumbing 100% Silicone Sealant

### PRODUCT DESCRIPTION

MONO<sup>®</sup> SILICONE MAX<sup>™</sup> Premium Kitchen, Bath & Plumbing 100% Silicone Sealant provides 20 year mould and mildew resistance. Won't crack or shrink, providing a durable, 100% waterproof seal. MONO SILICONE MAX is water ready in just 30 minutes. Once cured, it is safe for incidental food contact. Ideal for a wide variety of kitchen and bath applications such as sealing around sinks, tubs, showers, back splashes, countertops and fixtures. Sealant backed by a Lifetime Guarantee. Interior use.



PACKAGING	COLOUR	UPC
290 mL (9.8 fl oz.)	White	7079874832
290 mL (9.8 fl oz.)	Clear	7079874833
290 mL (9.8 fl oz.)	Translucent White	7079874861
290 mL (9.8 fl oz.)	Grey	7079874320
83 mL (2.8 oz)	White	7079874322
83 mL (2.8 oz)	Clear	7079874321

### KEY FEATURES & BENEFITS

- 20-year mould & mildew resistance
- Shower-ready in 30 minutes
- 100% waterproof seal
- Shrink and crack proof
- Certified by NSF to NSF / ANSI Standard #51
- Safe for incidental food contact. When cured and washed, the product meets the requirements of FDA Regulation No. 21 CFR 177.2600.
- Lifetime Guarantee
- Maximum flexibility
- Interior use



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## SUGGESTED USES

### USE FOR CAULKING AND SEALING:

- Showers
- Tubs
- Sinks
- Countertops
- Backsplashes
- Pipes
- Vents
- Fixtures
- Repairing loose tile

### ADHERES TO:

- Ceramic
- Porcelain
- Glass
- Cultured marble
- Vinyl
- Most plastics
- Most rubbers
- Most metals
- Fiberglass
- Wood – non-oily
- Drywall
- Plaster

## FOR BEST RESULTS

- Application temperature range is between -37 °C and 60 °C.
- Joint width should not exceed 13 mm (½"). If joint depth exceeds 13 mm (½"), use foam backer rod.
- Allow 24 hours for sealant to fully cure. Sealant will not cure in totally confined spaces.
- Corrodes some metals. \*Not recommended for use on or near brass, copper or copper alloys, zinc, iron, galvanized metals or other surfaces prone to attack by weak acids.
- Not recommended for filling butt joints, surface defects, tuck pointing, stovepipes, chimneys, fireplaces applications, continuous underwater use or oily woods and some metals. Not recommended for structural glazing.
- Not recommended on surfaces that might bleed oils, plasticizers or solvents. Best adhesion and compatibility are not achieved with substrates made of methyl methacrylate, polycarbonate, polypropylene, polyethylene or polytetrafluoroethylene. Evaluate such substrates before using sealant.
- **Not paintable.** Paint substrate surface before applying sealant.

## APPLICATION

### Surface Preparation

Surface must be clean, dry, structurally sound and free of all foreign material.

### Product Application

1. If using squeeze tube, remove cap & cut nozzle at 45° angle to desired bead size. Unscrew nozzle & remove foil seal. Replace nozzle. If using cartridge, cut nozzle at a 45° angle to desired bead size. Puncture inner foil seal. Load into caulk gun.
2. Fill gap or crack with sealant.
3. If necessary, tool or smooth the bead of sealant with a finishing tool before the sealant skins over.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- At 22 °C & 50% relative humidity, sealant is water resistant at 30 minutes & reaches full cure in 24 hours. Low humidity may slow cure.
- Clean up excess uncured sealant from surface and tools with mineral spirits or any other solvent. Scrape or cut away excess cured sealant. Do not use mineral spirits to clean skin. Wash hands or skin with soap and water.
- Sealant is not paintable. Paint surfaces prior to applying sealant.
- Reseal cartridge/tube for storage and reuse.

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

<b>Typical Uncured Physical Properties</b>	
Appearance/Consistency	Smooth paste
Base Polymer	Silicone rubber
Filler	Not applicable
Volatile	Not applicable
Weight % Solids	>97%
Specific Gravity	1.01
Odour	Vinegar like
Flash Point	>100°C
Freeze Thaw Stability (ASTM C1183)	Will not freeze
Shelf Life	24 months
Coverage	290 mL (9.8 fl. oz.): 14.8 linear metres at 5 mm diameter bead (53 linear feet at 3/16" diameter bead) 83 mL (2.8 fl. oz.): 4.2 linear metres at 5 mm diameter bead (15 linear feet at 3/16" diameter bead)
<b>Typical Application Properties</b>	
Application Temperature Range	-37 °C to 60 °C
Tooling Time (Working Time)	5 - 10 minutes
Tack Free Time	10 - 25 minutes
Full Cure	24 hours
Return to Service Time	30 minutes
Vertical Sag (ASTM D2202)	1.5 mm (0.05")
<b>Typical Cured Performance Properties</b>	
Service Temperature Range	-40 °C to 204 °C
Water Ready Time	30 minutes
Paint Ready Time	Not paintable
Mildew Resistance	20-year mould & mildew resistance guarantee



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## CLEAN UP & STORAGE

Remove excess uncured sealant from surfaces and tools with mineral spirits. Excess cured sealant must be cut or scraped away. Do not use mineral spirits to clean hands or skin. Wash hands or skin with soap and water. Store container in temperatures below 26 °C and in a dry place.

## SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.ca](http://dap.ca) or calling 888-327-8477.

## WARRANTY

DAP Canada, DAP Products Inc. and their respective affiliates will not accept liability for more than replacement product or sales price refund under any circumstances.

## COMPANY IDENTIFICATION

**Manufactured for:** DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON, M1X 1B7

**Usage Information:** Call 888-327-8477 or visit [dap.ca](http://dap.ca) & click on "Ask the Expert"

**Order Information:** 800-668-9397 or 416-321-1522

**Fax Number:** 416-321-3325

**Also visit the DAP website at [dap.ca](http://dap.ca)**