



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 03-22-11

## DAPtex<sup>®</sup> Plus Multi-Purpose Foam Sealant

- Seals, insulates and weatherproofs
- Easy water clean-up
- Won't overexpand
- Tough and durable
- Conserves energy to save money
- No paint thinner required
- Water resistant
- Paintable
- Toolable and moldable
- Reusable, non-clogging applicator
- Interior /Exterior

**Packaging:** Net Wt. 12oz (340g)  
**Color:** White  
**UPC Number:** 0 70798 18836 5, 0 70798 18822 8

### Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Baltimore, Maryland 21224  
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.  
Order Information: 800-327-3339  
Fax Number: 410-534-2650  
Also, visit the DAP website at [dap.com](http://dap.com).

### Product Description:

DAPtex<sup>®</sup> Plus Multi-Purpose Foam Sealant is a latex-based product used for filling voids and sealing large gaps. Designed to meet the tough standards demanded for professional window & door installations while offering the easiest-to-use technology for DIYers. When applied properly, this patented formula helps reduce energy loss and damage that can be caused by air, rain and pest infiltration.

### Suggested Uses:

#### Seals and Insulates:

- Windows
- Doors
- Ducts
- Pipes
- Vents
- Electrical Box Perimeters

#### Great for:

- Wood
- Concrete
- Brick
- Vinyl
- Steel
- Aluminum

### **Performance Characteristics:**

- **DAPtex<sup>®</sup> Plus** will not over expand like polyurethane foams. **DAPtex<sup>®</sup> Plus** will expand to 90% of its full size immediately upon application. Full expansion will be achieved within 20-30 minutes, depending on bead size, temperature and humidity.
- Proven not to bow, buckle or distort window and door frames.
- Tack free in 10 minutes. A one inch bead fully cures in 24 hours depending on bead size, temperature and humidity.
- Toolable and moldable while wet. Do not trim or remove skin of the cured foam.
- Flexible when cured.
- Cured foam can be painted with latex paint.
- Easy soap and water clean-up when wet.
- When fully cured the product should be firm to the touch and withstand moderate pressure.

### **Surface Preparation & Application:**

#### **INSTRUCTIONS: READ DIRECTIONS AND SAFETY INFORMATION BEFORE USE!**

1. Product is **EXTREMELY FLAMMABLE WHILE DISPENSING!** Refer to label and Material Safety Data Sheet and extinguish all ignition sources during use and cure.
2. To avoid risk of electric shock when perimeter sealing electrical switches and outlet boxes, disconnect power during application of product and until product is fully cured. \*When perimeter sealing switches or electrical boxes, do not fill box.
3. Wear safety glasses and use in well-ventilated areas.
4. Clean and remove grease, dirt and debris from application area.
5. Shake can vigorously for 1 minute before use.
6. Push straw into nozzle located above the trigger.
7. Remove safety tab above trigger.
8. Apply at temperatures between 45°F -105°F. The product should be above 60°F for optimum dispensing rate.
9. Slowly dispense foam from can in upright position, filling cavity to 90% to allow for minimal expansion.
10. For best results, tool or shape while wet. Do not trim or remove skin of the cured foam.
- 11. For exterior applications, foam must be painted with a quality exterior latex paint after fully cured.**
12. If storing for reuse, remove straw and clean it and nozzle with warm water. Cured material can be removed from nozzle or straw with a pipe cleaner or paper clip.
13. Not recommended for use at or below grade, or for closed cavities. For gaps more than 2" deep, use multiple layers of 1"-2" each.

### **Physical & Chemical Characteristics:**

Color	White
Consistency:	Foam (cured product has sponge-like consistency)
Vehicle:	Latex
Flash Point(of blowing agent):	<0°F
Flammability:	Level I Aerosol
Propellant:	Proprietary
Shelf Life:	12 Months when stored at 60-100°F
Temperature Service Range:	0°F to 150°F
Temperature Application Range:	45°F to 105°F (45°F and rising)
Packaging:	Standard – 12 oz. Aerosol Can
MSDS No.:	000 77344 003
Coverage:	One 12 oz. Can yields 510 feet at a 1/4" bead

### **Clean Up and Storage:**

Uncured foam can be cleaned up with soap and water. Excess cured sealant can be scraped off.

**Safety:**

See product label and Material Safety Data Sheet (MSDS) for complete safety information. You can request an MSDS by visiting our website at [dap.com](http://dap.com) or by calling 888-DAP-TIPS.

**Warranty Information:**

Buyer assumes all risks of use, handling and storage of product not in strict accordance with label directions. Liability for any incidental or consequential damages or loss is specifically excluded at all times. Any implied **warranty of fitness for a particular use** is excluded. Seller will not accept liability for more than product placement or purchase price refund.

An  Company