



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® Tank Bond™ Thread Stopper

### PRODUCT DESCRIPTION

**Tank Bond™ Thread Stopper** holds screws and bolts tightly in place so you can fix any loose screw. The fast-dry coating creates a tight seal that absorbs shock and vibrations preventing fasteners from unintentionally backing out of wood, metal, and plastic. Simply apply Thread Stopper to screw threads, let it dry, and install the screw into place. Treated fasteners remain completely adjustable, removable and reusable.



PACKAGING	COLOUR	UPC
6 mL	Red	7079874914

### KEY FEATURES & BENEFITS

- No Locking.
- Easy to Remove.
- Easy to Use Formula.

### PERFORMANCE CHARACTERISTICS

- Absorbs Shock and Vibrations.
- Remove & Reuse up to 5x.
- Multi Material: Wood, Metal, Plastic, & More.

### SUGGESTED USES

Can be used to prevent fasteners from loosening on furniture, door knobs, hinges, Eyewear frames, etc.  
Ideal for Bonding:

- Metal
- Plastic
- Wood

### APPLICATION

#### **Surface Preparation:**

1. Wear gloves to avoid skin contact.
2. Ensure parts are clean, dry and free from oil, grease, and foreign materials.
3. Shake tube to mix solution before applying.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

4. Remove cap and then cut tip as desired.

## **Application:**

1. Apply liquid to threaded surface, filling threads entirely. Temperature must be between 5 °C to 48 °C for application.
2. Allow liquid coating to dry for 30 minutes.
3. Thread on nut and apply gel to either side of threaded component.

Note: It is recommended that DAP Tank Bond Thread Stopper be tested in the application for which it is to be used.

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Adhesive Base:	Acrylic Resins
Consistency:	Viscous liquid
Colour:	Red
Non-Volatiles:	30%
Flash Point:	16 °C
Density:	1.09 g/cm <sup>3</sup>
Application Temperature Range:	5 °C to 48 °C
Service Temperature Range:	-53 °C to 73 °C
Full Cure (for assembly):	30 mins
Shelf Life:	24 Months Minimum @ 21 °C

## CLEAN UP & STORAGE

Keep container closed when not in use. Keep product away from all sources of ignition, heat or flame. Store product in a cool, dry place.

## SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.ca](http://dap.ca). or calling 888-DAP-TIPS.

## WARRANTY

DAP Canada, DAP Products Inc. and their respective affiliates will not accept liability for more than replacement product or sales price refund under any circumstances



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## COMPANY IDENTIFICATION

**Manufactured for:** DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON, M1X 1B7

**Usage Information:** Call 888-DAP-TIPS or visit [dap.ca](http://dap.ca) & click on "Ask the Expert"

**Order Information:** 800-668-9397 or 416-321-1522

**Fax Number:** 416-321-3325

**Also visit the DAP website at [dap.ca](http://dap.ca)**